

**Application:**

Construction industry – Industry – Communities

- for jetting wellpoints, wells or piles
- for water supply at construction sites
- to fill and test pipe lines
- to clean construction vehicles and equipment
- for fire fighting
- for irrigation

**Design:**

HÜDIG high pressure pumps are multistaged, normalpriming centrifugal pumps, suitable for pumping clean or slightly dirty water without solids. The pumps are driven by Diesel engine and are hand-primed.

- mounted on single-axle trailer with pneumatic tyres, therefore may be driven on sites (6 km/h)
- removable truck draw bar
- battery box and crane hook eye
- sturdy welded steel-tankframe-chassis
- extra large capacity fuel tank

**Pump:**

$V_{max}$ : 60,0 m³/h  
 $p_{max}$ : 16,3 bar  
 Connection: suction side 108 male –  
 discharge side 50 male  
 4 stages

**Engine:**

Brand: DEUTZ  
 Type: F 3L1011F  
 Capacity: 32,5 kW  
 Speed: 2900 min<sup>-1</sup>

Weight: 645 kg  
 Dimension: length: 1930 mm x width: 1360 mm x height: 1750 mm

Subject to change without notice!

## HÜDIG - your partner to solve water problems.

### HÜDIG®

GmbH &amp; Co. KG

**Absenk- und Berechnungsanlagen**

Heinrich-Hüdig-Straße 2 · 29227 Celle  
 Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18  
 e-mail: Info@huedig.de